



## OAK EARTH

The smoked finish on this single-strip oak floor from the Artisan Collection enhances the natural colour variations for a rustic expression. Knots and cracks pepper the boards, adding depth and balancing the toasted sesame seed highlights. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

### PRODUCT DETAILS

Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	151XCDEKFCWK195 / 7393969045261
Design / Wood Species	1-strip / Oak
Surface treatment / Natural/Stained	Oil / Natural
Design features	Bevelled 4-sided, Brushed, Smoked, Handscraped
Width x Length x Thickness	190 x 1900 x 15 mm
Weight per package / per m2	17 kg / 7.83 kg
Area per package / per pallet	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Backside material	Veneer

### PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	30 years

### TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



### DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

**Oil:** This floor should be oiled immediately after installation.

**Colour change:** The smoked finish accentuates the natural color variations, creating a stronger contrast between light and dark tones initially. Over time, the color variations will soften, resulting in a more uniform overall appearance. The oiled surface will develop a natural patina.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2025-08-09

Other products in this collection



OAK BUCKSKIN



MAPLE CAROB



OAK CONCRETE



OAK STRAW



OAK OYSTER



OAK EARTH



OAK CAMINO