



OAK FARTH

The smoked finish on this single-strip oak floor from the Artisan Collection enhances the natural colour variations for a rustic expression. Knots and cracks pepper the boards, adding depth and balancing the toasted sesame seed highlights. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9
Article Number / EAN Code	151XCDEKFCKW195 / 7393969045261	range	
Design / Wood Species	Plank / Oak	Warranty	30 years
Surface treatment /	Oil / Natural	TECHNICAL PROPERTIES	
Natural/Stained		Moisture content	EN13183
Design features	Bevelled 4-sided, Brushed, Smoked,	Minimun Mean Density —— kg/m³	
	Handscraped		
Width x Length x Thickness	190 x 1900 x 15 mm	Reaction To Fire	EN13501-1
Weight per package / per	17 kg / 7.83 kg	Formaldehyde Emission	EN717-1
m2		Content PCP	CEN/TR14823
Area per package / per	2.17 m ² / 75.95 m ²	Breaking Strength N/mm²	EN1533
pallet		Thermal Conductivity	EN12664
Grading	Dynamic	Biological Durability	EN350-2
Joint	Woodloc® 5G	— CARB2	
Installation method	Floating, Glue-down	Slip resistance	CEN/TS15676
Floor heating	Yes		CEIV/1313070
Wear leayer material /	Hardwood / 3.5 mm	TSCA TITLE VI	EMESSIONS DANS LYAM INTERBURY
thickness		CARB P2	A
Resandable	2-3 times	Compliant BASIA	
Core material	Pine/Spruce		
Backside material	Veneer		

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: The smoked finish accentuates the natural color variations, creating a stronger contrast between light and dark tones initially. Over time, the color variations will soften, resulting in a more uniform overall appearance. The oiled surface will develop a natural patina.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection







MAPLE CAROB




OAK CONCRETE



OAK STRAW







OAK EARTH



OAK CAMINO