



OAK EARTH

A rustic, handscraped product. Smoking gives the board a dark brown impression, a big colour variation can occur. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer engineered	
Article Number / EAN Code	151XCDEKFCKW195 / 7393969045261	
Design / Wood Species	1-strip / White Oak	
Surface Treatment /	Oil / Natural	
Natural/Stained		
Refining Treatment	Beveled 4-sided, Brushed, Smoked,	
	Handscraped	
Width x Length x Thickness	7 1/2 x 74 3/4 x 5/8"	
Weight per package / per	37.5 lbs / 17.3 lbs	
m2		
Area per package / per	23.4 sqft / 817.5 sqft	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5G	
Installation method	Floating, Glue-Down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 1/8"	
thickness		
Resandable	2 times	
Core material	Pine/Spruce lamella	

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





DETAILED DESCRIPTION

Warranty

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

25 years

Packages may contain start and stop boards.

