



## OAK DOVE

The whisper white overtones in this single-strip, oak floor from the Prime collection enhances the stone hues in the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	141XACEK1WKW190 / 7393969045063	range		
Design / Wood Species	1-strip / White Oak	— TECHNICAL PROPERTIES		
Surface Treatment /	Matte finish / Stained	Moisture content	EN13183	7%±2%
Natural/Stained		— Minimun Mean Density		>500 kg/m <sup>3</sup>
Refining Treatment	Microbeveled 4-sided, Brushed	— kg/m³		O
Width x Length x Thickness	7 1/2 x 73 1/4 x 1/2"	Reaction To Fire	EN13501-1	Dfl-s1
Weight per package / per	50.7 lbs / 18.1 lbs	Formaldehyde Emission	EN717-1	E1
m2		— Content PCP	CFN/TR14823	≤ 5 x 10-6n
Area per package	30.1 sqft	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Grading	Lively	— Thermal Conductivity	EN12664	0.14 W/mK
Joint	Woodloc®	— Thermal Resistance R-Value		.10 (m2K/W)
Installation method	Floating, Glue-Down	Biological Durability	EN350-2	Class 1
Floor heating	Yes		EINSSU-Z	
Wear leayer material /	Hardwood / 1/8"	— CARB2	CENTEGA E CO	Compliant
thickness		Slip resistance	CEN/TS15676	NPD
Resandable	2 times			
Core material	Pine/Spruce			
Backside material	Veneer	<del></del>		

## DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and fillings. Knots and fillings may vary in size and numbers.

**Colour change**: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

