



## **OAK MELLOW**

The pale, sandy-brown hues in this single-strip, oak floor from the Prime Collection balances the subtle colour variation in the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel.

| PRODUCT DETAILS             |                                 | PRODUCT DETAILS                     |                 |                        |
|-----------------------------|---------------------------------|-------------------------------------|-----------------|------------------------|
| Product type / Construction | Wood Floors / 3-layer parquet   | Hardness (Brinell) value /          | 3,7 / 2.2 - 5.9 |                        |
| Article Number / EAN Code   | 141XACEK1VKW190 / 7393969045056 | range                               |                 |                        |
| Design / Wood Species       | Plank / Oak                     | Warranty                            | 30 years        |                        |
| Surface treatment /         | Matt lacquer / Stained          | TECHNICAL PROPERTIES                |                 |                        |
| Natural/Stained             |                                 | — Moisture content                  | FN13183         | 7%±2%                  |
| Design features             | Microbevelled 4-sided, Brushed  | — Minimun Mean Density              | 21113103        | >500 kg/m <sup>3</sup> |
| Width x Length x Thickness  | 189 x 1860 x 14 mm              | — kg/m <sup>3</sup>                 |                 | >300 Kg/III            |
| Weight per package / per    | 23 kg / 8.21 kg                 | Reaction To Fire                    | EN13501-1       | Dfl-s1                 |
| m2                          |                                 | Formaldehyde Emission               | EN717-1         | E1                     |
| Area per package            | 2.8 m <sup>2</sup>              | — Content PCP                       | CEN/TR14823     | ≤ 5 ppm                |
| Grading                     | Lively                          | Breaking Strength N/mm <sup>2</sup> | EN1533          | NPD                    |
| Joint                       | Woodloc®                        | — Thermal Conductivity              | EN12664         | 0,14 W/mK              |
| Installation method         | Floating, Glue-down             | — Thermal Resistance R-Value        |                 | •                      |
| Floor heating               | Yes                             |                                     |                 | .10 (m2K/W)            |
| Wear leayer material /      | Hardwood / 3 mm                 | Biological Durability               | EN350-2         | Class 1                |
| thickness                   |                                 | CARB2                               |                 | Compliant              |
| Resandable                  | 2-3 times                       | Slip resistance                     | CEN/TS15676     | NPD                    |
| Core material               | Pine/Spruce                     |                                     |                 |                        |
| Backside material           | Veneer                          |                                     |                 |                        |

## DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and fillings. Knots and fillings may vary in size and numbers.

**Colour change**: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

