



OAK NORDERNEY

This rustic single-strip with a misty white oil features knots and cracks for an effortlessly rustic expression. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 151N9AEKF1KW240 / 7393969045148 |
| Design / Wood Species | 1-strip / Oak |
| Surface treatment / Natural/Stained | Oil / Stained |
| Design features | Brushed, Microbevelled 4-sided |
| Width x Length x Thickness | 187 x 2420 x 15 mm |
| Weight per package / per m2 | 22 kg / 8.15 kg |
| Area per package / per pallet | 2.72 m ² / 122.4 m ² |
| Grading | Dynamic |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear leayer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce/Alder |
| Backside material | Spruce |

PRODUCT DETAILS

| | |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| Warranty | 30 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kährs.com | ©Kährs

2025-08-25

Other products in this collection



OAK AMALFI



OAK RÜGEN



OAK ESTORIL



OAK SORRENTO



OAK PORTOFINO



OAK BRIGHTON



ASH SKAGEN



ASH SANDVIG



ASH FALSTERBO