



## OAK MENTON

This 2-strip oak floor from the Sand Collection features warm tones highlighted by a white pigmented matt lacquer for a contemporary expression with subtle contrasts in the planks. The light finish enhances the even grade of the boards, resulting in a soft and smooth appearance.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9
Article Number / EAN Code	152N3BEKB1KW240 / 7393969043946	range	
Design / Wood Species	2-strip / Oak	LRV / LRV Std1	47 / 3.1
Surface treatment /	Matt lacquer / Stained	Warranty	30 years
Natural/Stained		TECHNICAL PROPERTIES	
Design features	Brushed	— Moisture content	EN13183
Width x Length x Thickness	200 x 2423 x 15 mm	— Minimun Mean Density	LIVISIOS
Weight per package / per	23 kg / 7.93 kg	kg/m <sup>3</sup>	
m2		— Reaction To Fire	EN13501-1
Area per package / per	2.9 m <sup>2</sup> / 130.1 m <sup>2</sup>	Formaldehyde Emission	EN717-1
pallet		— Content PCP	CEN/TR14823
Grading	Variation	Breaking Strength N/mm²	FN1533
Joint	Woodloc® 5S	Thermal Conductivity	EN12664
Installation method	Floating, Glue-down	— Thermal Resistance R-Value	LIN12004
Floor heating	Yes		EN350-2
Wear leayer material /	Hardwood / 3.5 mm	Biological Durability	EIN35U-Z
thickness		CARB2	
Resandable	2-3 times	Slip resistance	CEN/TS15676
Core material	Pine/Spruce/Alder	TSCA BESWAN SOL	® UNESION CLASE
Backside material	Spruce	CARB P2	M1> 3

Hardness (Brinell) value /	3,//2.2 - 5.9
range	
LRV / LRV Std1	47 / 3.1
Warranty	30 years
TECHNICAL DDODEDTIES	

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



















## DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticable color change over time

Packages may contain start and stop boards.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

## Other products in this collection



OAK AMALFI



OAK RÜGEN



OAK NORDERNEY



OAK ESTORIL



OAK SORRENTO



OAK PORTOFINO



OAK BRIGHTON



ASH SKAGEN



ASH SANDVIG



ASH FALSTERBO