



OAK SHORE

The mineral grey notes in this single-strip oak floor from the Lux Collection are awash with subtle earth tones, eloquently complemented by the ultra-matt lacquer finish. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

Article Number / EAN Code 151N8AEKE4KW240 / 7393969044219 r Design / Wood Species 1-strip / Oak L	PRODUCT DETAILS		P
Design / Wood Species 1-strip / Oak Surface treatment / Ultra matt lacquer / Stained Natural/Stained Design features Microbevelled 4-sided, Brushed Width x Length x Thickness 187 x 2420 x 15 mm Weight per package / per 22 kg / 8.15 kg m2 Area per package / per 2.72 m² / 122.4 m² pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm Surface treatment / Hardwood / 3.5 mm Lively Suppose	Product type / Construction	Wood Floors / 3-layer parquet	F
Surface treatment / Ultra matt lacquer / Stained Design features Microbevelled 4-sided, Brushed Width x Length x Thickness 187 x 2420 x 15 mm Weight per package / per 22 kg / 8.15 kg m2 Area per package / per 2.72 m² / 122.4 m² Fallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm Surface treatment / Victorian Microbevelled 4-sided, Brushed Micro	Article Number / EAN Code	151N8AEKE4KW240 / 7393969044219	r
Natural/Stained Design features Microbevelled 4-sided, Brushed Midth x Length x Thickness 187 x 2420 x 15 mm Weight per package / per 22 kg / 8.15 kg m2 Area per package / per 2.72 m² / 122.4 m² Fading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm Sepandable Core material Pine/Spruce/Alder	Design / Wood Species	1-strip / Oak	L
Design features Microbevelled 4-sided, Brushed Width x Length x Thickness 187 x 2420 x 15 mm Weight per package / per 22 kg / 8.15 kg m2 Area per package / per 2.72 m² / 122.4 m² pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm Shape of the side of the	Surface treatment /	Ultra matt lacquer / Stained	V
Width x Length x Thickness 187 x 2420 x 15 mm Weight per package / per 22 kg / 8.15 kg m2 Area per package / per 2.72 m² / 122.4 m² pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Natural/Stained		т
Weight per package / per 22 kg / 8.15 kg m2 Area per package / per 2.72 m² / 122.4 m² pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Design features	Microbevelled 4-sided, Brushed	<u>_</u>
m2 Area per package / per 2.72 m² / 122.4 m² pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Width x Length x Thickness	187 x 2420 x 15 mm	
m2 Area per package / per 2.72 m² / 122.4 m² pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Weight per package / per	22 kg / 8.15 kg	N
pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	m2		R
pallet Grading Lively Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Area per package / per	2.72 m ² / 122.4 m ²	
Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	pallet		<u>'</u>
Joint Woodloc® 5S Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Grading	Lively	
Floor heating Yes Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Joint	Woodloc® 5S	
Wear leayer material / Hardwood / 3.5 mm thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Installation method	Floating, Glue-down	
thickness Resandable 2-3 times Core material Pine/Spruce/Alder	Floor heating	Yes	
Resandable2-3 timesCore materialPine/Spruce/Alder	Wear leayer material /	Hardwood / 3.5 mm	
Core material Pine/Spruce/Alder	thickness		3
	Resandable	2-3 times	
Backside material Spruce	Core material	Pine/Spruce/Alder	
	Backside material	Spruce	

PRO	DUCI	DET	AILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1	30 / 2.7	
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



















DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection

