



OAK ECLIPSE

The mineral grey notes in this 3-strip oak floor from the Lumen Collection are awash with stoney earth tones, eloquently complemented by the ultra-matt lacquer finish. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS

| | |
|----------------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 153N3BEKE4KW240 / 7393969044288 |
| Design / Wood Species | 3-strip / Oak |
| Surface treatment / | Ultra matt lacquer / Stained |
| Natural/Stained | |
| Design features | Brushed |
| Width x Length x Thickness | 200 x 2423 x 15 mm |
| Weight per package / per m2 | 23 kg / 7.93 kg |
| Area per package / per pallet | 2.91 m ² / 130.1 m ² |
| Grading | Variation |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear leayer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce/Alder |
| Backside material | Spruce |

PRODUCT DETAILS

| | |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| LRV / LRV Std1 | 24 / 2.5 |
| Warranty | 30 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticeable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2026-01-11

Other products in this collection



OAK GLOW



OAK VAPOR



OAK DIM



OAK RIME



OAK MIST



OAK TWILIGHT



OAK ECLIPSE



OAK DAWN



OAK DUSK