



OAK SKY

DDODUCT DETAIL O

The semi-transparent white stain on this single-strip oak floor from the Lux Collection balances the light and dark contrasts in the wood, allowing the subtle warm oak tones to softly filter through. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		PRODUCT DET
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinel
Article Number / EAN Code	151N8AEKB4KW240 / 7393969044189	range
Design / Wood Species	1-strip / Oak	LRV / LRV Std1
Surface Treatment /	Ultra matt lacquer / Stained	Warranty
Natural/Stained		— TECHNICAL PR
Refining Treatment	Microbevelled 4-sided, Brushed	— Moisture conten
Width x Length x Thickness	187 x 2420 x 15 mm	— Minimun Mean D
Weight per package / per	22 kg / 8.15 kg	kg/m ³
m2		Reaction To Fire
Area per package / per	2.72 m ² / 122.4 m ²	Formaldehyde E
pallet		Content PCP
Grading	Lively	Breaking Strengt
Joint	Woodloc® 5S	— Biological Durabi
Installation method	Floating, Glue-down	— CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 3.5 mm	Jilp resistance
thickness		AND SION CLASE SPREAM DAVE LAW
Resandable	2-3 times	
Core material	Pine/Spruce/Alder	.47.kM 04.
Backside material	Spruce	

PRODUCT	DETAILS
---------	---------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1	44 / 2.8	
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1

kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD
·		•







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time

Packages may contain start and stop boards.

Other products in this collection

