



OAK COAST

This single-strip, stained oak floor from the Lux Collection features warm, earth tones pooled with stone grey hues. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet	Brinell value / range	3,7 / 2.2 - 5.9
Article Number / EAN Code	151N8AEKD4KW240 / 7393969044202	LRV / LRV Std1	28 / 2.9
Design / Wood Species	1-strip / Oak	Warranty	30 years
Surface Treatment /	Ultra matt lacquer / Stained	TECHNICAL PROPERTIES	
Natural/Stained		— Moisture content	EN13183
Refining Treatment	Microbevelled 4-sided, Brushed	-	LIVISIOS
Width x Length x Thickness	187 x 2420 x 15 mm	—— Minimun Mean Density —— kg/m³	
Weight per package / per	22 kg / 8.15 kg	Reaction To Fire	EN13501-1
<u>m2</u>		Formaldehyde Emission	EN717-1
Area per package / per	2.7 m ² / 122.4 m ²	Content PCP	CEN/TR14823
pallet		Breaking Strength N/mm ²	EN1533
Grading	Lively	Thermal Conductivity	EN12664
Joint	Woodloc® 5S	— Thermal Resistance R-Value	
Installation method	Floating, Glue-down	Biological Durability	EN350-2
Floor heating	Yes	— CARB2	LINSSU-Z
Wear leayer material /	Hardwood / 3.5 mm	-	
thickness		Slip resistance	CEN/TS15676
Resandable	2-3 times	M1) 2 SCORE SCORE	
Core material	Pine/Spruce/Alder		
Backside material	Spruce		

PRODU	JCT D	ETAI	LS

Brinell value / range	3,7 / 2.2 - 5.9	
LRV / LRV Std1	28 / 2.9	
Warranty	30 years	
TECHNICAL PROPERTIES	,	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	!	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery

NPD

Other products in this collection

