



OAK TFRRA

This single-strip oak floor from the Lux Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) valu
Article Number / EAN Code	151N8AEKF4KW240 / 7393969044226	range
Design / Wood Species	1-strip / Oak	LRV / LRV Std1 / LRV S
Surface treatment /	Ultra matt lacquer / Natural	Warranty
Natural/Stained		— TECHNICAL PROPE
Design features	Microbevelled 4-sided, Brushed, Smoked	Moisture content
Width x Length x Thickness	187 x 2420 x 15 mm	Minimun Mean Densit
Weight per package / per	22 kg / 8.15 kg	
m2		— Reaction To Fire
Area per package / per	2.72 m ² / 122.4 m ²	Formaldehyde Emission
pallet		— Content PCP
Grading	Lively	Breaking Strength N/n
Joint	Woodloc® 5S	Thermal Conductivity
Installation method	Floating, Glue-down	Biological Durability
Floor heating	Yes	— CARB2
Wear leayer material /	Hardwood / 3.5 mm	
thickness		Slip resistance
Resandable	2-3 times	TSCA TITLE VI
Core material	Pine/Spruce/Alder	CARB P2
Backside material	Spruce	Compliant

PRODUCT	DETAILS
---------	---------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1 / LRV Std2	16 / 3.3 / 6.6	
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD









CEN/TS15676

EN12664

EN350-2





0,11W/mK

Compliant

Class 1

NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances the natural colour variations and creates a stronger contrast between light and dark.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Smoked product - noticable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection

