



OAK TERRA

This single-strip oak floor from the Lux Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DETAILS | | PRODUCT DETAILS | |
|-----------------------------|--|--|------|
| Product type / Construction | Wood Flooring / 3-layer parquet | Hardness (Brinell) value / | 3,7 |
| Article Number / EAN Code | 151N8AEKF4KW240 / 7393969044226 | range | |
| Design / Wood Species | 1-strip / Oak | LRV / LRV Std1 / LRV Std2 | 16 / |
| Surface Treatment / | Ultra matt lacquer / Natural | Warranty | 30 ½ |
| Natural/Stained | | — TECHNICAL PROPERTIES | |
| Refining Treatment | Microbevelled 4-sided, Brushed, Smoked | Moisture content | EN1 |
| Width x Length x Thickness | 187 x 2420 x 15 mm | Minimun Mean Density kg/m³ | |
| Weight per package / per | 22 kg / 8.15 kg | | |
| m2 | | — Reaction To Fire | EN1 |
| Area per package / per | 2.72 m ² / 122.4 m ² | Formaldehyde Emission | EN7 |
| pallet | | — Content PCP | CEN |
| Grading | Lively | Breaking Strength N/mm ² | EN1 |
| Joint | Woodloc® 5S | Biological Durability | EN3 |
| Installation method | Floating, Glue-down | — CARB2 | L140 |
| Floor heating | Yes | — Slip resistance | CEN |
| Wear leayer material / | Hardwood / 3.5 mm | | CLIV |
| thickness | | MESION COASE PRINCIPLO COMPLETE PRINCIPLO FILE | |
| Resandable | 2-3 times | M1) A+ SCOTE | |
| Core material | Pine/Spruce/Alder | | |
| Backside material | Spruce | | |

| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
|----------------------------|-----------------|------------|
| range | | |
| LRV / LRV Std1 / LRV Std2 | 16 / 3.3 / 6.6 | |
| Warranty | 30 years | |
| TECHNICAL PROPERTIE | S | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Donation To Fire | EN13E01 1 | Dfl c1 |

| , | 0 | |
|-------------------------------------|-------------|-------------|
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Smoked product - noticable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection

