



OAK TERRA

This single-strip oak floor from the Lux Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS

Article Number	151N8AEKF4KW240
EAN Code	7393969044226
Surface Treatment	Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles.
Refining Treatment	Microbevelled 4-sided, Brushed, Smoked
Dimensions	187 x 2420 mm
Weight per Package	22 kg
Area per Package	2.7 m ²
Area per pallet	122.4 m ²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances.

COLOUR CHANGE

Smoked product - noticeable color change over time

FACTS

Wood Species	Oak
Design	1-strip
Grading	Lively
Range	Kährs Original
Collection	Lux Collection
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Pine/Spruce/Alder
Backside material	Spruce
Installation method	Floating, Glue-down
Surface Colour	Brown
LRV	16

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m ³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m ² K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Oak Crayon



Oak Biscotti



Oak Ghost



Oak Eggshell



Ash Stream



Ash Flow



Oak Sky



Oak Horizon



Oak Coast



Oak Shore



Oak Sun



Oak Terra

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.