



OAK TERRA

This single-strip oak floor from the Lux Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brinell) value /	3,7 / 2.2 - 5.9
Article Number / EAN Code	151N8AEKF4KW240 / 7393969044226	range	
Design / Wood Species	1-strip / White Oak	LRV / LRV Std1 / LRV Std2	16 / 3.3 / 6.6
Surface Treatment /	Ultra matt lacquer / Natural	TECHNICAL PROPERTIES	
Natural/Stained		Moisture content	EN13183
Refining Treatment	Microbeveled 4-sided, Brushed, Smoked		EINIOO
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"	— Minimun Mean Density — kg/m³	
Weight per package / per	48.5 lbs / 18 lbs	Reaction To Fire	EN13501-1
m2		— Formaldehyde Emission	EN717-1
Area per package / per	29.3 sqft / 1317.5 sqft	Content PCP	CEN/TR14823
pallet		Breaking Strength N/mm²	EN1533
Grading	Lively	·	EN350-2
Joint	Woodloc® 5S	Biological Durability	EN330-2
Installation method	Floating, Glue-Down	— CARB2	CENTEGAT CO.
Floor heating	Yes	— Slip resistance CEN/TS15676	
Wear leayer material /	Hardwood / 1/8"	TSCA SESWAN ECOL SINSSION CLASS	floor -
thickness		CARB P2	score (E
Resandable	2 times	Compliant Office	Common av Services
Core material	Pine/Spruce/Alder		
Backside material	Spruce	<u> </u>	

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1 / LRV Std2	16 / 3.3 / 6.6	_
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Packages may contain start and stop boards.

Other products in this collection









OAK CRAYON

OAK BISCOTTI

OAK GHOST

OAK EGGSHELL



OAK TERRA