



## OAK TRENCH

A misty-grey stain gives this single-strip oak floor from the Rugged Collection a calm and pared-back feel, while knots and cracks create a rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

### PRODUCT DETAILS

<b>Article Number</b>	101P8HEKFMKW180
<b>EAN Code</b>	7393969043793
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Microbevelled 4-sided, Brushed, Handscraped
<b>Dimensions</b>	1830 x 125 x 10 mm
<b>Weight per Package x</b>	16,75 kg
<b>Area per Package (m<sup>2</sup>)</b>	1.8
<b>Area per pallet (m<sup>2</sup>)</b>	0
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Rugged Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1.9 mm
<b>Core material</b>	HDF
<b>Thickness</b>	10 mm
<b>Surface Colour</b>	Grey FM
<b>Installation method</b>	Floating, Glue-down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>800 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Cfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.07 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*