



Götaland Collection



## OAK ATTEBO

The cigarillo brown nuances featured in this 3-strip oak floor from the Götaland Collection are enhanced by flashes of rich charcoal and burnt embers, resulting in a moderately rich colour variation and a refined expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

### PRODUCT DETAILS

|                                     |   |
|-------------------------------------|---|
| Product type / Construction         | Wood Floors / 3-layer parquet                     |
| Article Number / EAN Code           | 153N66EK04KW240 / 7393969042789                   |
| Design / Wood Species               | 3-strip / Oak                                     |
| Surface treatment / Natural/Stained | Oil / Stained                                     |
| Design features                     | Bevelled 4-sided, Handscraped, Brushed, Saw marks |
| Width x Length x Thickness          | 196 x 2419 x 15 mm                                |
| Weight per package / per m2         | 22.4 kg / 7.89 kg                                 |
| Area per package / per pallet       | 2.84 m <sup>2</sup> / 127.8 m <sup>2</sup>        |
| Grading                             | Dynamic   |
| Joint                               | Woodloc® 5S                                       |
| Installation method                 | Floating, Glue-down                               |
| Floor heating                       | Yes   |
| Wear leayer material / thickness    | Hardwood / 3.5 mm                                 |
| Resandable                          | 2-3 times   |
| Core material                       | Pine/Spruce/Alder                                 |
| Backside material                   | Spruce  |

### PRODUCT DETAILS

|                                  |                 |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| Warranty                         | 30 years        |

### TECHNICAL PROPERTIES

|                                     |             |                        |
|-------------------------------------|-------------|------------------------|
| Moisture content                    | EN13183     | 7%±2%                  |
| Minimun Mean Density                |             | >500 kg/m <sup>3</sup> |
| Reaction To Fire                    | EN13501-1   | Dfl-s1                 |
| Formaldehyde Emission               | EN717-1     | E1                     |
| Content PCP                         | CEN/TR14823 | ≤ 5 ppm                |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                    |
| Thermal Conductivity                | EN12664     | 0,11W/mK               |
| Biological Durability               | EN350-2     | Class 1                |
| CARB2                               |             | Compliant              |
| Slip resistance                     | CEN/TS15676 | NPD                    |



### DETAILED DESCRIPTION

Contains knots and all natural colour variations.

**Oil:** This floor should be oiled immediately after installation.

**Colour change:** The colour matures over time

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2025-08-25

Other products in this collection



OAK VINGA