



SAFARI

PRODUCT DETAILS

Article Number	101P8QEKFKKW180
EAN Code	7393969043809
Surface Treatment	Oil This floor should be oiled immediately after installation.
Refining Treatment	Microbevelled 4-sided, Smoked, Saw marks
Dimensions	1830 x 125 x 10 mm
Weight per Package	16.80 kg
Area per Package	1.80 m ²
Area per pallet (m²)	0.00 m ²
Package info	Packages may contain start and stop boards.

COLOUR CHANGE

Smoked product - little colour change.

FACTS

Wood Species	Oak
Design	1-strip
Grading	Dynamic
Range	Kährs Spirit
Collection	Rugged Collection
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc®
Floor heating	Yes
Wear-layer material	Hardwood
Core material	HDF
Thickness	10 mm
Installation method	Floating, Glue-down

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>800 kg/m ³	
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.07 (m ² K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.