



OAK HUSK

DDODLICT DETAIL C

Tawny shades are interspersed with pronounced, charred-brown knots in this single-strip oak floor from the Rugged Collection. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

| PRODUCT DETAILS | | |
|-----------------------------|---|--|
| Product type / Construction | Wood Floors / Veneer floors | |
| Article Number / EAN Code | 101P8HEKF0KW180 / 7393969043816 | |
| Design / Wood Species | 1-strip / Oak | |
| Surface treatment / | Oil / Natural | |
| Natural/Stained | | |
| Design features | Microbevelled 4-sided, Brushed, Handscraped | |
| Width x Length x Thickness | 125 x 1830 x 10 mm | |
| Weight per package / per | 16.8 kg / 9.33 kg | |
| m2 | | |
| Area per package | 1.8 m ² | |
| Grading | Dynamic | |
| Joint | Woodloc® | |
| Installation method | Floating, Glue-down | |
| Floor heating | Yes | |
| Wear leayer material / | Hardwood / 1.9 mm | |
| thickness | | |
| Resandable | 1 time | |
| Core material | HDF | |
| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| range | | |

PRODUCT DETAILS

| Warranty | 20 years | |
|-------------------------------------|-------------|-------------|
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >800 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Cfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | 2 | .07 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |











DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | [©]Kährs 2025-07-01

Other products in this collection



OAK MOON