



# OAK HUSK

Tawny shades are interspersed with pronounced, charred-brown knots in this single-strip oak floor from the Rugged Collection. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

| PRODUCT DETAILS                     |   | TECHNICAL PROPERTIES                |             |                        |
|-------------------------------------|---|-------------------------------------|-------------|------------------------|
| Product type / Construction         | Wood Flooring / Veneer floors               | Moisture content                    | EN13183     | 7%±2%                  |
| Article Number / EAN Code           | 101P8HEKF0KW180 / 7393969043816             | Minimun Mean Density                |             | >800 kg/m <sup>3</sup> |
| Design / Wood Species               | 1-strip / Oak                               | kg/m <sup>3</sup>                   |             |                        |
| Surface Treatment / Natural/Stained | Oil / Natural                               | Reaction To Fire                    | EN13501-1   | Cfl-s1                 |
| Refining Treatment                  | Microbevelled 4-sided, Brushed, Handscraped | Formaldehyde Emission               | EN717-1     | E1                     |
| Width x Length x Thickness          | 125 x 1830 x 10 mm                          | Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n            |
| Weight per package / per m2         | 16.8 kg / 9.33 kg                           | Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                    |
| Area per package                    | 1.8 m <sup>2</sup>                          | Thermal Conductivity                | EN12664     | 0,14 W/mK              |
| Grading                             | Dynamic                                     | Thermal Resistance R-Value          |             | .07 (m2K/W)            |
| Joint                               | Woodloc®                                    | Biological Durability               | EN350-2     | Class 1                |
| Installation method                 | Floating, Glue-down                         | CARB2                               |             | Compliant              |
| Floor heating                       | Yes   | Slip resistance                     | CEN/TS15676 | NPD                    |
| Wear leayer material / thickness    | Hardwood / 1.9 mm                           |                                     |             |                        |
| Core material                       | HDF   |                                     |             |                        |
| Hardness (Brinell) value / range    | 3,7 / 2.2 - 5.9                             |                                     |             |                        |
| Warranty                            | 20 years                                    |                                     |             |                        |



## DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

- Oil:** This floor should be oiled immediately after installation.
- Colour change:** Some muting of colour variation to medium, straw brown.
- Packages may contain start and stop boards.

Other products in this collection



OAK MOON