



ATELIER OAK CD WHITE 11 MM

Offered with a variety of surface treatments and patterns. Sapwood included.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	111PCDEK0VKE120	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969043465	Design	1-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface treatment	Matt lacquer	Grading	Lively	Reaction To Fire	EN13501-1	Cfl-s1
Design features	Brushed, Microbevelled 4-sided	Range	Kährs Master	Formaldehyde Emission	EN717-1	E1
Dimensions	120 x 1200 mm	Collection	Atelier Collection	Content PCP	CEN/TR14823	≤ 5 ppm
Weight per Package	9.4 kg	Resandable	2 times	Breaking Strength N/mm²	EN1533	NPD
Area per Package	1.4 m²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Brinell Value	3,7	Thermal Resistance R-Value		.08 (m2K/W)
DETAIL DESCRIPTION		Joint	Tongue & Groove	Biological Durability	EN350-2	Class 1
Normal colour variation, knots and cracks allowed, sap wood allowed.		Floor heating	Yes	CARB2		Compliant
COLOUR CHANGE		Warranty	30 years	Slipperiness	CEN/TS15676	NPD
Stained product - little colour change.		Wear-layer material	Hardwood			
		Wear Layer Thickness	3.5 mm			
		Thickness	11 mm			
		Installation method	Glue-down			
		Surface Colour	White			

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.