



FOSSIL

This single-strip oak floor from the Rugged Collection has been lightly smoked to create an authentically aged look. Rustic knots and cracks mottle the golden-grey planks and the stain brings a milky hue. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS

Article Number	101P8HEKFHKW180
EAN Code	7393969043823
Surface treatment	Oil This floor should be oiled immediately after installation.
Design features	Microbevelled 4-sided, Brushed, Light smoked, Handscraped
Dimensions	125 x 1830 mm
Weight per Package	16.8 kg
Area per Package	1.8 m ²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

COLOUR CHANGE

Stained product - noticable color change over time.


FACTS

Wood Species	Oak
Design	1-strip
Grading	Dynamic
Range	Kährs Spirit
Collection	Rugged Collection
Resandable	1 time
Natural/Stained	Stained
Brinell Value	3,7
Joint	Woodloc®
Floor heating	Yes
Warranty	20 years
Warranty US	20 years
Wear-layer material	Hardwood
Wear Layer Thickness	1.9 mm
Core material	HDF
Thickness	10 mm
Installation method	Glue-down, Floating
Surface Colour	Grey RFH

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>800 kg/m ³	
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.07 (m ² K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD


Other products in this collection




Oak Moon




Walnut Groove




Oak Trench



Oak Crater



Oak Fossil



Oak Husk



Oak Safari

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.