



## ATELIER OAK CD WHITE 11 MM

Offered with a variety of surface treatments and patterns. Sapwood inlcuded.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	111PCDEKFVKE120	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969043458	Design	1-strip	content		
Surface treatment	Oil This floor should be oiled immediately after installation.	Grading	Lively	Minimun Mean Density kg/m³ >500 kg/m³		
		Range	Kährs Master	Reaction To Fire	EN13501-1	Cfl-s1
		Collection	Atelier Collection	Formaldehyde Emission	EN717-1	E1
Design features	Brushed, Microbevelled 4-sided	Resandable	2 times			
		Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 ppm
Dimensions	120 x 1200 mm	Brinell Value	3,7	Breaking	EN1533	NPD
Weight per Package	9.4 kg	Joint	Tongue & Groove	Strength N/mm²		
Area per Package	1.4 m <sup>2</sup>	Floor heating	Yes	Thermal	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Warranty	30 years	Conductivity		
		Wear-layer material	Hardwood	Thermal Resistance R-Value		.08 (m2K/W)
DETAIL DESCRIPTION		Wear Layer Thickness	3.5 mm	Biological Durability	EN350-2	Class 1
Normal colour variation, knots and cracks allowed, sap wood allowed.  COLOUR CHANGE		Thickness	11 mm	CARB2		Compliant
		Installation method	Glue-down		CEN/TS15676	Compliant
		Surface Colour	White	Slipperiness	CEIN/13130/0	NFD

Stained product - little colour change.

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.