



OAK KILESAND

The natural grain of the wood in this 3-strip oak floor from the Götaland Collection is enhanced by pastel grey and white notes in the knots and cracks, resulting in an organic expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	153N66EK05KW240 / 7393969042819
Design / Wood Species	3-strip / Oak
Surface treatment /	Oil / Stained
Natural/Stained	
Design features	Bevelled 4-sided, Handscraped, Brushed, Saw
	marks
Width x Length x Thickness	196 x 2419 x 15 mm
Weight per package / per	22.4 kg / 7.89 kg
m2	
Area per package / per	2.84 m ² / 127.8 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce/Alder
Backside material	Spruce

PRODUCT	DETAILS
---------	---------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

















DETAILED DESCRIPTION

Contains knots and all natural colour variations.

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection



OAK VINGA