



KILESAND

White nuances from bread and flour creates contrast that accentuates the natural grain of the wood.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153N66EK05KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969042819	Design	3-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic			
		Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	Götaland Collection	Formaldehyde Emission	EN717-1	E1
Refining Treatment	Bevelled 4-sided, Handscraped, Brushed, Saw marks	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	196 x 2419 mm	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
Weight per Package	22.4 kg	Joint	Woodloc® 5S	Thermal Conductivity	EN12664	0,14 W/mK
Area per Package	2.84 m²	Floor heating	Yes			
Area per pallet	127.8 m²		25 years	Thermal Resistance R-Value	.11 (m2K/W)	
Package info	Packages may contain start and stop boards.	Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
		Wear Layer Thickness	3.5 mm	CARB2 Compliant		
		Core material	Pine/Spruce/Alder			
DETAIL DESCRIPTION	Contains knots and all natural colour variations.	Backside material	Spruce	Slipperiness	CEN/TS15676	NPD
			15 mm			
			Installation method	Floating, Glue-down		
COLOUR CHANGE		Surface Colour	White			

DETAIL DESCRIPTION

Contains knots and all natural colour variations.

COLOUR CHANGE

The colour matures over time

Other products in this collection



Boda



Backa



Vinga



Attebo



Kilesand

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.