

## CRATER

The knotted, cinnamon-brown planks of this single-strip floor in the Rugged Collection, have been smoked to create an authentically aged expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer 10 mm	Warranty	20 years	
Article Number / EAN Code	101P8HEKFCKW180 / 7393969043830	— TECHNICAL PROPERTIES	:	
Design / Wood Species	1-strip / Oak	— Moisture content	, EN13183	7%±2%
Surface treatment /	Oil / Natural	Minimun Mean Density	ENTSTOS	>800 kg/m <sup>3</sup>
Natural/Stained		— kg/m <sup>3</sup>		>000 kg/11
Design features	Microbevelled 4-sided, Brushed, Smoked,	Reaction To Fire	EN13501-1	Cfl-s1
	Handscraped			
Width x Length x Thickness	125 x 1830 x 10 mm	Formaldehyde Emission	EN717-1	E1
Weight per package / per	16.8 kg / 9.33 kg	— Content PCP	CEN/TR14823	≤ 5 ppm
m2		Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area per package	1.8 m <sup>2</sup>	Thermal Conductivity	EN12664	0,14 W/mK
Grading	Dynamic	— Thermal Resistance R-Value		.07 (m2K/W)
loint	Woodloc®	<ul> <li>Biological Durability</li> </ul>	EN350-2	Class 1
5		— CARB2		Compliant
Installation method	Floating, Glue-down	— Slip resistance	CEN/TS15676	NPD
Floor heating	Yes			
Wear leayer material /	Hardwood / 1.9 mm		Bressen DANE LAR HYDROUP	
thickness		CARB P2		
Resandable	1 time	Compliant *32WW ON BASIA	<b>A</b>	
Core material	HDF			
Hardness (Brinell) value /	3,7 / 2.2 - 5.9			
range				

## DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection





Oak Trench



Oak Crater



Oak Fossil



Oak Husk