



# CRATER

The knotted, cinnamon-brown planks of this single-strip floor in the Rugged Collection, have been smoked to create an authentically aged expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

## PRODUCT DETAILS

<b>Article Number</b>	101P8HEKFCKW180
<b>EAN Code</b>	7393969043830
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Microbevelled 4-sided, Brushed, Smoked, Handscraped
<b>Dimensions</b>	125 x 1830 mm
<b>Weight per Package</b>	16.8 kg
<b>Area per Package</b>	1.8 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

## DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.

## COLOUR CHANGE

Smoked product - noticeable color change over time.


## FACTS

<b>Wood Species</b>	Oak
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Rugged Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Natural
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Warranty US</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	1.9 mm
<b>Core material</b>	HDF
<b>Thickness</b>	10 mm
<b>Installation method</b>	Floating, Glue-down
<b>Surface Colour</b>	Brown FS

## TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>800 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Cfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.07 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slipperiness</b>	CEN/TS15676	NPD


## Other products in this collection



Oak Moon




Walnut Groove




Oak Trench



Oak Crater



Oak Fossil



Oak Husk



Oak Safari

## CERTIFICATES



## Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*