



OAK CRATER

The knotted, cinnamon-brown planks of this single-strip floor in the Rugged Collection, have been smoked to create an authentically aged expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / Veneer floors	
Article Number / EAN Code	101P8HEKFCKW180 / 7393969043830	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Natural	
Natural/Stained		
Refining Treatment	Microbevelled 4-sided, Brushed, Smoked,	
	Handscraped	
Width x Length x Thickness	125 x 1830 x 10 mm	
Weight per package / per	16.8 kg / 9.33 kg	
m2		
Area per package	1.8 m ²	
Area per package Grading	1.8 m ² Dynamic	
Grading	Dynamic	
Grading Joint	Dynamic Woodloc®	
Grading Joint Installation method	Dynamic Woodloc® Floating, Glue-down	
Grading Joint Installation method Floor heating	Dynamic Woodloc® Floating, Glue-down Yes	
Grading Joint Installation method Floor heating Wear leayer material /	Dynamic Woodloc® Floating, Glue-down Yes	
Grading Joint Installation method Floor heating Wear leayer material / thickness	Dynamic Woodloc® Floating, Glue-down Yes Hardwood / 1.9 mm	
Grading Joint Installation method Floor heating Wear leayer material / thickness Core material	Dynamic Woodloc® Floating, Glue-down Yes Hardwood / 1.9 mm	

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>800 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.07 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection



OAK MOON