



# **CRATER**

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	101P8HEKFCKW180	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969043830	Design	1-strip	content		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Minimun Mean Density kg/m³ >800 kg/m		
		Range	Kährs Spirit	Reaction To Fire	EN13501-1	Cfl-s1
		Collection	Rugged Collection	Formaldehyde Emission	EN717-1	E1
Refining Treatment	Microbevelled 4-sided, Brushed, Smoked, Handscraped	Natural/Stained	Natural			
		Brinell Value	3,7	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	125 x 1830 mm	Joint	Woodloc®	Breaking Strength N/mm²	EN1533	NPD
Weight per Package	16.8 kg	Floor heating	Yes			
Area per Package	1.8 m <sup>2</sup>		20 years	Thermal	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Wear-layer material	Hardwood	Conductivity		
		Wear Layer Thickness	1.9 mm	Thermal Resistance R-Value		.07 (m2K/W)
DETAIL DESCRIPTION		Core material	HDF	Biological  Durability	EN350-2	Class 1
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and			10 mm	CARB2		Compliant
		Installation method	Floating, Glue-down	Slipperiness	CEN/TS15676	

## COLOUR CHANGE

and is permitted without restriction.

Smoked product - noticable color change over time.

black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design

### Other products in this collection





Trench





Fossil

Moon





Husk Safari

#### CERTIFICATES







#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.