

CRATER

PRODUCT DETAILS F/		FACTS		TECHNICAL PROPERTIES		
101P8HEKFCKW180	Wood Species	White Oak	Moisture	EN13183	7%±2%	
7393969043830	Design	1-strip	content			
Surface Treatment Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Minimun Mean Density kg/m ³ >800 kg/m ³			
	Range	Kährs Spirit	Reaction To Fire	EN13501-1	Cfl-s1	
	Collection	Rugged Collection	Formaldehyde Emission	EN717-1	E1	
Refining Treatment Microbeveled 4-sided, Brushed, Smoked, Handscraped	Resandable	1 time				
	Natural/Stained	Natural	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
4 7/8 x 72 "	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD	
37 lbs	Joint	Woodloc®				
19.4 sqft	Floor heating	Yes	Thermal	EN12664	0,14 W/mK	
Package infoPackages may containstart and stop boards.	Warranty	20 years	Conductivity			
	Warranty	20 years	Thermal Resistance R-Value .07		.07 (m2K/W)	
	Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1	
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and		1/8"			Compliant	
		HDF		CEN/TS15676	•	
		3/8"	Subbermess			
	7393969043830OilThis floor should be oiled immediately after installation.Microbeveled 4-sided, Brushed, Smoked, Handscraped4 7/8 x 72 "37 lbs19.4 sqftPackages may contain start and stop boards.ood colour variations rk brown. Sapwood may des very large sound and	101P8HEKFCKW180Wood Species7393969043830DesignOilGradingThis floor should be oiled immediately after installation.GradingMicrobeveled 4-sided, Brushed, Smoked, HandscrapedResandable4 7/8 x 72 "Brinell Value37 lbsJoint19.4 sqftFloor heatingPackages may contain start and stop boards.WarrantyWear-layer materialWear Layer Thicknesscool colour variations rk brown. Sapwood may des very large sound andThialacace	101P8HEKFCKW180Wood SpeciesWhite Oak7393969043830Design1-stripOil This floor should be oiled immediately after installation.GradingDynamicMicrobeveled 4-sided, Brushed, Smoked, HandscrapedResandable1 time4 7/8 x 72 "Brinell Value3,737 lbsJointWoodloc®19.4 sqftFloor heatingYesPackages may contain start and stop boards.Warranty20 yearsWarranty20 yearsWear-layer materialHardwoodWear Layer Thickness1/8"Colour variations rk brown. Sapwood may des very large sound andThialacaca2/8"	101P8HEKFCKW180Wood SpeciesWhite OakMoisture content7393969043830Design1-stripMinimun MeanOil This floor should be oiled immediately after installation.GradingDynamicReaction To FireMicrobeveled 4-sided, Brushed, Smoked, HandscrapedResandable1 timeFormaldehyde EmissionMicrobeveled 4-sided, Brushed, Smoked, HandscrapedResandable1 timeContent PCP4 7/8 x 72 "Brinell Value3,7Breaking Strength N/mm2Breaking Strength N/mm237 lbsJointWoodloc®Thermal Conductivity19.4 sqftFloor heating Warranty20 yearsThermal Biological DurabilityPackages may contain start and stop boards.Warranty20 yearsBiological Durabilityood colour variations rk brown. Sapwood may des very large sound andHDFSilipperiness	101P8HEKFCKW180Wood SpeciesWhite OakMoisture contentEN131837393969043830Design1-stripMinimun Mean Density kg/m³Oil This floor should be oiled immediately after installation.GradingDynamicReaction To FireEN13501-1Microbeveled 4-sided, Brushed, Smoked, HandscrapedResandable1 timeFormaldehyde EN717-1EN717-1Microbeveled 4-sided, Brushed, Smoked, HandscrapedResandable1 timeContent PCPCEN/TR148234 7/8 x 72 "Brinell Value3,7Breaking Strength N/mm²EN153337 lbsJointWoodloc®Thermal ConductivityEN1266419.4 sqftFloor heating WarrantyYesThermal ConductivityEN12664Packages may contain start and stop boards.Warranty20 yearsEn12664Wear-layer material rk brown. Sapwood may des very large sound andHDFEN350-2Doid Core materialHDFSlipperinessCEN/TS15676	

Installation method Floating, Glue-Down

COLOR CHANGE

Smoked product - noticable color change over time.

will be present in all sizes and numbers. Any flaking

in the wood-surface is due to the hand-crafting technique used on the surface to create the design

and is permitted without restriction.



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.