



## OAK BODA

The warm, golden tones in this 3-strip oak floor from the Götaland Collection are punctuated by naturally occurring knots and cracks, resulting in a timeless and classic expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

Product type / Construction Wood Floors / 3-layer parquet  Article Number / EAN Code 153N66EK01KW240 / 7393969042772  Design / Wood Species 3-strip / Oak  Surface treatment / Oil / Natural	— ; — ;
Design / Wood Species 3-strip / Oak	_ _ ; 
Surface treatment / Oil / Natural	
Natural/Stained	
Design features Bevelled 4-sided, Handscraped, Brushed, Sav	/
marks	
Width x Length x Thickness 196 x 2419 x 15 mm	
Weight per package / per 22.4 kg / 7.89 kg	
m2	
Area per package / per 2.84 m² / 127.8 m²	•
pallet	:
Grading Dynamic	
Joint Woodloc® 5S	
Installation method Floating, Glue-down	_
Floor heating Yes	
Wear leayer material / Hardwood / 3.5 mm	
thickness	
Resandable 2-3 times	
Core material Pine/Spruce/Alder	
Backside material Spruce	

PRC	DU	CT	DE.	ΓΑΙ	LS

Hardness (Brinell) Value /	3,//2.2 - 5.9
range	
Warranty	30 years

## **TECHNICAL PROPERTIES**

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

















Contains knots and all natural colour variations.

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time Packages may contain start and stop boards.

Descriptions & Imagery

## Other products in this collection



OAK VINGA