



BACKA

Rich and warm tones from amber creates a generous and luxurious ambiance.

PRODUCT DETAILS

Article Number	153N66EK02KW240
EAN Code	7393969042796
Surface Treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Handscraped, Brushed, Saw marks
Dimensions	196 x 2419 mm
Weight per Package	22.4 kg
Area per Package	2.84 m ²
Area per pallet	127.8 m ²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION

Contains knots and all natural colour variations.

COLOUR CHANGE

The colour matures over time

FACTS

Wood Species	Oak
Design	3-strip
Grading	Dynamic
Range	Kährs Original
Collection	Götaland Collection
Natural/Stained	Stained
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Pine/Spruce/Alder
Backside material	Spruce
Thickness	15 mm
Installation method	Floating, Glue-down


TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m ³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m ² K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD


Other products in this collection



Boda



Backa



Vinga



Attebo



Kilesand

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.