



# BACKA

Rich and warm tones from amber creates a generous and luxurious ambiance.

## PRODUCT DETAILS

<b>Article Number</b>	153N66EK02KW240
<b>EAN Code</b>	7393969042796
<b>Surface Treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Refining Treatment</b>	Bevelled 4-sided, Handscraped, Brushed, Saw marks
<b>Dimensions</b>	2419 x 196 x 15 mm
<b>Weight per Package</b>	22.4 kg
<b>Area per Package</b>	2.8 m <sup>2</sup>
<b>Area per pallet (m<sup>2</sup>)</b>	113.6 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

## FACTS

<b>Wood Species</b>	Oak
<b>Design</b>	3-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Original
<b>Collection</b>	Götaland Collection
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Wear-layer material</b>	Hardwood
<b>Core material</b>	Pine/Spruce/Alder
<b>Thickness</b>	15 mm
<b>Installation method</b>	Floating, Glue-down

## TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	

## DETAIL DESCRIPTION

Contains knots and all natural colour variations.

## COLOUR CHANGE

The colour matures over time



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*