OAK VINGA

The pale grey hues featured in this 3-strip oak floor from the Götaland Collection reveal natural warm undertones resulting in a temperate expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	153N66EK03KW240 / 7393969042802
Design / Wood Species	3-strip / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Bevelled 4-sided, Handscraped, Brushed, Saw marks
Width x Length x Thickness	196 x 2419 x 15 mm
Weight per package / per m2	22.4 kg / 7.89 kg
Area per package / per pallet	2.84 m² / 127.8 m²
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Pine/Spruce/Alder
Backside material	Spruce

PRODUCT DETAILS

Brinell value / range	3,7 / 2.2 - 5.9
Warranty	30 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

Contains knots and all natural colour variations.

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time

Packages may contain start and stop boards.

Other products in this collection

Oak Boda

Oak Backa

Oak Vinga

Oak Attebo

Oak Kilesand