



OAK VINGA

Light cold greys that appear to have been worn down, revealing the natural oak base.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	153N66EK03KW240 / 7393969042802
Design / Wood Species	3-strip / Oak
Surface Treatment / Natural/Stained	Oil / Stained
Refining Treatment	Bevelled 4-sided, Handscraped, Brushed, Saw marks
Width x Length x Thickness	196 x 2419 x 15 mm
Weight per package / per m2	22.4 kg / 7.89 kg
Area per package / per pallet	2.84 m ² / 127.8 m ²
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Pine/Spruce/Alder
Backside material	Spruce

PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	30 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Contains knots and all natural colour variations.

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK VINGA