



OAK VINGA

Light cold greys that appear to have been worn down, revealing the natural oak base.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	153N66EK03KW240 / 7393969042802
Design / Wood Species	3-strip / Oak
Surface Treatment /	Oil / Stained
Natural/Stained	
Refining Treatment	Bevelled 4-sided, Handscraped, Brushed, Saw
	marks
Width x Length x Thickness	196 x 2419 x 15 mm
Weight per package / per	22.4 kg / 7.89 kg
m2	
Area per package / per	2.84 m ² / 127.8 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce/Alder
Backside material	Spruce

PRODUCT D	ETAILS
-----------	--------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

Contains knots and all natural colour variations.

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time Packages may contain start and stop boards.

Other products in this collection



OAK VINGA