



# VINGA

Light cold greys that appear to have been worn down, revealing the natural oak base.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153N66EK03KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969042802	Design	3-strip	Minimum Mean Density kg/m³	>500 kg/m³	
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic			
		Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	Götaland Collection	Formaldehyde Emission	EN717-1	E1
Refining Treatment	Bevelled 4-sided, Handscraped, Brushed, Saw marks	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	196 x 2419 mm	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
		Joint	Woodloc® 5S	Thermal Conductivity	EN12664	0,14 W/mK
Weight per Package	22.4 kg	Floor heating	Yes			
Area per Package	2.84 m²		25 years	Biological Durability	EN350-2	Class 1
Area per pallet	127.8 m²	Wear-layer material	Hardwood	CARB2	Compliant	
Package info	Packages may contain start and stop boards.	Wear Layer Thickness	3.5 mm	Slipperiness	CEN/TS15676	NPD
		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
DETAIL DESCRIPTION	Contains knots and all natural colour variations.		15 mm			
		Installation method	Floating, Glue-down			
COLOUR CHANGE						
The colour matures over time						

Other products in this collection



Boda



Backa



Vinga



Attebo



Kilesand

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*