



Accessories / Installation / **Installation**

# FLOOR UNDERLAYER 2 MM

Underlayer for reduction of impact- and airborne sound. This product works well over floor heating systems.  
Ideal for floating parquet and laminate flooring  
Polyethylene foam with closed cells and fine cell structure for high compression strength and Impact Sound improvement  
Light, strong and flexible  
Makes the floor more comfortable to walk on  
Suitable in connection with the floor heating systems  
Age resistance > 50 years  
100% recyclable

Material: Polyethylene  
Density: 30 kg/m3  
Impact Sound IS: 15 - 19 Db  
Compressive strength CS: 22,7 kPa  
Compressive creep CC: 2,4 kPa  
Punctual conformability PC: 1,5 mm  
Thermal resistance TR: 0,045 m2K/W  
Water vapor resistance SD: 10,9 m

## Product details

Article Number	710184
Name	FLOOR UNDERLAYER 2 MM
EAN Code	7393969236850
	Installation
Length	50000 mm
Width	1200 mm
	2 mm

**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*