



OAK PALE

The semi-transparent, white finish on this 3-strip oak floor from the Harmony Collection allow the warmer nuances to come through, perfect for a light, Nordic-style interior. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

| | |
|--------------------|---|
| Article Number | 153N5BEKP1KW240 |
| EAN Code | 7393969041775 |
| Surface treatment | Matt lacquer |
| Design features | Brushed |
| Dimensions | 200 x 2423 mm |
| Weight per Package | 23 kg |
| Area per Package | 2.9 m ² |
| Area per pallet | 130.1 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|----------------------|---------------------|
| Wood Species | Oak |
| Design | 3-strip |
| Grading | Variation |
| Range | Kährs Original |
| Collection | Harmony Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Warranty US | 25 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Backside material | Spruce |
| Thickness | 15 mm |
| Installation method | Floating, Glue-down |
| Surface Colour | White |

TECHNICAL PROPERTIES

| | | |
|--|------------------------|-----------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m ³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slipperiness | CEN/TS15676 | NPD |

Other products in this collection



Oak Silk



Oak Shell



Oak Brownie



Oak Alloy



Oak Pale



Oak Ale



Oak Creme



Oak Granite



Oak Cirrus



Oak Dew



Oak Soil



Oak Stone



Oak Limestone



Oak Lava

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.