



## OAK CHEVRON DARK BROWN

The richly smoked finish on this ready-to-install, patterned oak board from the Chevron Collection enhances its deeply burnished hue, and brings a modern expression to its traditional look. Each board is carefully brushed to bring out the natural character of the grain and highlight the texture of the wood. Partial handcrafting gives each board its unique appearance, while micro-bevelling enhances the iconic geometric design. This is a frame board which is supplied in form of a plank, it can be used to create a boarder around the Chevron patterned design. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

### PRODUCT DETAILS

Article Number	151XADEKWFKW190
EAN Code	7393969041829
Surface treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Brushed, Smoked
Dimensions	148 x 1900 mm
Weight per Package	18.2 kg
Area per Package	2.3 m <sup>2</sup>
Area per pallet	108 m <sup>2</sup>
Package info	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Smoked product - noticeable color change over time.

### FACTS

Wood Species	Oak
Design	Pattern
Grading	Lively
Range	Kährs ID
Collection	Chevron Collection
Resandable	2-3 times
Natural/Stained	Stained
Brinell Value	3,7
Joint	Tongue & Groove
Floor heating	Yes
Warranty	30 years
Warranty US	20 years
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Poplar
Backside material	Oak
Thickness	15 mm
Installation method	Glue-down
Surface Colour	Dark brown

### TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m <sup>3</sup>	>500 kg/m <sup>3</sup>	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Oak Chevron Dark brown



Oak Chevron Light brown



Oak Chevron Grey

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*