



ALE

With it's saturated, rich and warm nuances, this floor creates a generous and luxurious ambiance.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	153N6CEKQ1KW240 / 7393969041799	range
Design / Wood Species	3-strip / Oak	Warranty
Surface Treatment /	Matt lacquer / Stained	TECHNICAL PROPERTIES
Natural/Stained		— Moisture content
Refining Treatment	Brushed	— Minimun Mean Density
Width x Length x Thickness	200 x 2423 x 15 mm	— kg/m ³
Weight per package / per	23 kg / 7.93 kg	Reaction To Fire
<u>m2</u>		Formaldehyde Emission
Area per package / per	2.9 m ² / 130.1 m ²	Content PCP
pallet		Breaking Strength N/mm ²
Grading	Lively	— Thermal Conductivity
Joint	Woodloc® 5S	— Thermal Resistance R-Value
Installation method	Floating, Glue-down	Biological Durability
Floor heating	Yes	— CARB2
Wear leayer material /	Hardwood / 3.5 mm	
thickness		Slip resistance
Resandable	2-3 times	MESION CLASS MISSONS CANS INTEREST FLOOR
Core material	Pine/Spruce lamella	M1) A+ score
Backside material	Spruce	- 3√VM O/4.

PRODUCT	DETAILS
----------------	---------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant





CEN/TS15676

NPD

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur.

The product includes large sound and black knots and cracks. Knots and cracks may vary in size and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection

Oak Lava

Oak Limestone

