



ALE

With it's saturated, rich and warm nuances, this floor creates a generous and luxurious ambiance.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153N6CEKQ1KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969041799	Design	3-strip	Minimum Mean Density kg/m³		
Surface Treatment	Matt lacquer	Grading	Lively	>500 kg/m ³		
Refining Treatment	Brushed	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	200 x 2423 mm	Collection	Harmony Collection	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.9 m ²	Brinell Value	3,7	Breaking Strength N/mm ²	EN1533	NPD
Area per pallet	130.1 m ²	Joint	Woodloc® 5S	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION			25 years	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Wear Layer Thickness	3.5 mm	Slipperiness	CEN/TS15676	NPD
		Core material	Pine/Spruce lamella			
		Backside material	Spruce			
COLOUR CHANGE			15 mm			
		Installation method	Floating, Glue-down			
Stained product - noticable color change over time.		Surface Colour	Warm brown			

Other products in this collection



Oak Shell



Brownie



Alloy



Pale



Ale



Oak Dew



Oak Soil



Oak Stone



Oak Limestone



Oak Lava

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.