



ASH SANDVIG

This single-strip ash floor from the Sand Collection features the natural, warm core of the timber creating a pleasant contrast with the powder light hues. The naturally occurring knots and colour variations in the grain are prominent give this floor a unique expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

Wood Flooring / 3-layer parquet
151L87AK0VKW220 / 7393969041621
1-strip / Ash
Matt lacquer / Stained
187 x 2266 x 15 mm
21 kg / 8.4 kg
2.5 m ² / 114.3 m ²
Lively
Woodloc® 5S
Floating, Glue-down
Yes
Hardwood / 3.5 mm
2-3 times
Pine/Spruce lamella
4,0 / 2.8 - 6.2
60.7 / 11.4

PRC	DU	CT	DE.	ΓΑΙ	LS

Warranty	30 years	
TECHNICAL PROPERTIES		
- Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
- kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
- CARB2		Compliant
- Slip resistance	CEN/TS15676	NPD

















Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes large sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection



Oak Amalfi



Oak Rügen



Oak Norderney



Oak Estoril



Oak Sorrento



Oak Portofino



Oak Brighton



Ash Skagen



Ash Sandvig



Ash Falsterbo