



ASH SANDVIG 226

DDODLICT DETAILS

This single-strip ash floor from the Sand Collection features the natural, warm core of the timber creating a pleasant contrast with the powder light hues. The naturally occurring knots and colour variations in the grain are prominent give this floor a unique expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	151L87AK0VKW220 / 7393969041621
Design / Wood Species	1-strip / Ash
Surface Treatment /	Matt lacquer / Stained
Natural/Stained	
Width x Length x Thickness	187 x 2266 x 15 mm
Weight per package / per	21 kg / 8.4 kg
m2	
Area per package / per	2.54 m ² / 114.3 m ²
pallet	
Grading	Lively
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce
Hardness (Brinell) value /	4,0 / 2.8 - 6.2
range	
LRV / LRV Std1	61 / 11.4

000	LICT	DETAIL	_
PROD	UCI	DETAIL	_S

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes large sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Kahrs (UK) Ltd |

2025-11-01

Other products in this collection



OAK ESTORIL



OAK SORRENTO



OAK PORTOFINO



OAK BRIGHTON



ASH SKAGEN



ASH SANDVIG



ASH FALSTERBO