



OAK ALLOY

A light gray with earth tones that works well as a base for a variety of interior styles. The sap wood elements breathe life and variation into the surface.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	153N0BEKD1KW240 / 7393969041751	
Design / Wood Species	3-strip / Oak	
Surface Treatment /	Matt lacquer / Stained	
Natural/Stained		
Refining Treatment	Brushed	
Width x Length x Thickness	200 x 2421 x 15 mm	
Weight per package / per	23 kg / 7.9 kg	
m2		
Area per package / per	2.91 m ² / 130.1 m ²	
pallet		
Grading	Lively	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-3 times	
Core material	Pine/Spruce	
Backside material	Spruce	

PRODU	ICT D	ETAI	LS

_	_
Warranty	30 years
LRV / LRV Std1	26 / 3.6
range	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9

- TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur.

The product includes large sound and black knots and cracks. Knots and cracks may vary in size and numbers. Brown, grey and white putty is used to fill cracks and knot holes.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection









OAK BROWNIE

OAK ALLOY

OAK PALE

OAK ALE



OAK LIMESTONE