



## **ALLOY**

A light gray with earth tones that works well as a base for a variety of interior styles. The sap wood elements breathe life and variation into the surface.

PRODUCT DETAILS		PRODUCT D
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brir
Article Number / EAN Code	153N0BEKD1KW240 / 7393969041751	range
Design / Wood Species	3-strip / White Oak	LRV / LRV Std1
Surface Treatment /	Matte finish / Stained	Warranty
Natural/Stained		— TECHNICAL I
Refining Treatment	Brushed	Moisture cont
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"	— Minimun Mea
Weight per package / per	50.7 lbs / 17.4 lbs	kg/m <sup>3</sup>
m2		Reaction To Fi
Area per package / per	31.3 sqft / 1400.4 sqft	Formaldehyde
pallet		Content PCP
Grading	Lively	Breaking Strer
Joint	Woodloc® 5S	— Biological Dura
Installation method	Floating, Glue-Down	— CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 1/8"	Jilp resistance
thickness		TSCA TITLE VI
Resandable	2 times	CARB P2
Core material	Pine/Spruce lamella	Compliant
Backside material	Spruce	

3,7 / 2.2 - 5.9	
26 / 3.6	
25 years	
EN13183	7%±2%
	>500 kg/m³
EN13501-1	Dfl-s1
EN717-1	E1
CEN/TR14823	≤ 5 x 10-6n
EN1533	NPD
EN350-2	Class 1
	Compliant
CEN/TS15676	NPD
	26 / 3.6 25 years EN13183 EN13501-1 EN717-1 CEN/TR14823 EN1533 EN350-2









## DETAILED DESCRIPTION

The product includes large sound and black knots and cracks. Knots and cracks may vary in size and numbers. Brown, grey and white putty is used to fill cracks and knot holes.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection







Oak Pale

Oak Limestone