




OAK ALLOY

The owl grey hues in this 3-strip oak floor from the Harmony Collection create a peaceful expression, punctuated by naturally occurring color variations in the timber. Each board is carefully brushed to bring out the character of the grain and highlight the texture of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

| | |
|-------------------------------------|------------------------------------|
| Product type / Construction | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code | 153N0BEKD1KW240 / 7393969041751 |
| Design / Wood Species | 3-strip / White Oak |
| Surface Treatment / Natural/Stained | Matte finish / Stained |
| Refining Treatment | Brushed |
| Width x Length x Thickness | 7 7/8 x 95 3/8 x 5/8" |
| Weight per package / per m2 | 50.7 lbs / 17.4 lbs |
| Area per package / per pallet | 31.3 sqft / 1400.4 sqft |
| Grading | Lively |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-Down |
| Floor heating | Yes |
| Wear leayer material / thickness | Hardwood / 1/8" |
| Resandable | 2 times |
| Core material | Pine/Spruce |
| Backside material | Spruce |

PRODUCT DETAILS

| | |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| LRV / LRV Std1 | 26 / 3.6 |
| Warranty | 25 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur.

The product includes large sound and black knots and cracks. Knots and cracks may vary in size and numbers. Brown, grey and white putty is used to fill cracks and knot holes.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK PALE



OAK LIMESTONE