



# OAK STUDIO AB MATT

Oak Studio AB Matt, a 2-layer construction, is a clean oak with some colour variation and small knots with a matt finish.

## PRODUCT DETAILS

|                                     |  |
|-------------------------------------|--|
| Product type / Construction         | Wood Flooring / 2-layer parquet            |
| Article Number / EAN Code           | 111PABEK09KE050 / 7393969042130            |
| Design / Wood Species               | Herringbone / Oak                          |
| Surface Treatment / Natural/Stained | Matt lacquer / Natural                     |
| Width x Length x Thickness          | 70 x 490 x 11 mm                           |
| Weight per package / per m2         | 13.3 kg / 6.33 kg                          |
| Area per package / per pallet       | 2.06 m <sup>2</sup> / 123.6 m <sup>2</sup> |
| Grading                             | Calm                                       |
| Joint                               | Tongue & Groove                            |
| Installation method                 | Glue-down                                  |
| Floor heating                       | Yes  |
| Wear layer material / thickness     | Hardwood / 3.5 mm                          |
| Core material                       | Pine lamella                               |
| Hardness (Brinell) value / range    | 3,7 / 2.2 - 5.9                            |
| Warranty                            | 30 years                                   |

## TECHNICAL PROPERTIES

|                                     |             |                          |
|-------------------------------------|-------------|--------------------------|
| Moisture content                    | EN13183     | 7%±2%                    |
| Minimum Mean Density                |             | >500 kg/m <sup>3</sup>   |
| Reaction To Fire                    | EN13501-1   | Cfl-s1                   |
| Formaldehyde Emission               | EN717-1     | E1                       |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10 <sup>-6</sup> n |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                      |
| Thermal Conductivity                | EN12664     | 0,14 W/mK                |
| Thermal Resistance R-Value          |             | .08 (m <sup>2</sup> K/W) |
| Biological Durability               | EN350-2     | Class 1                  |
| CARB2                               |             | Compliant                |
| Slip resistance                     | CEN/TS15676 | NPD                      |

## TECHNICAL PROPERTIES

### DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

**Colour change:** Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |  
www.kahrs.com | ©Kährs,  
United Kingdom & Ireland  
2025-07-01

## Other products in this collection



OAK STUDIO AB WHITE MATT



OAK STUDIO AB OILED



OAK STUDIO CD HB MATT



OAK STUDIO CD HB OILED



OAK STUDIO AB WHITE OILED



OAK STUDIO AB SMOKED



OAK STUDIO AB MATT