



OAK STUDIO AB WHITE OILED

Oak AB White, a 2-layer construction, is a oak floor with colour variations and small knots with a white matt finish. The product is delivered with both left and right version in the bundles for herringbone installation.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Floors / 2-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	111PABEKFVKE050 / 7393969042383	Minimun Mean Density		>500 kg/m³
Design / Wood Species	Herringbone / Oak	kg/m³		
Surface treatment /	Oil / Stained	Reaction To Fire	EN13501-1	Cfl-s1
Natural/Stained		Formaldehyde Emission	EN717-1	E1
Width x Length x Thickness	70 x 490 x 11 mm	Content PCP	CEN/TR14823	≤ 5 ppm
Weight per package / per	13.3 kg / 6.33 kg	Breaking Strength N/mm²	EN1533	NPD
m2		Thermal Conductivity	EN12664	0,14 W/mK
Area per package / per	2.06 m ² / 123.6 m ²	Thermal Resistance R-Value		.08 (m2K/W)
pallet		Biological Durability	EN350-2	Class 1
Grading	Calm	CARB2		Compliant
Joint	Tongue & Groove	Slip resistance	CEN/TS15676	NPD
Installation method	Glue-down			
Floor heating	Yes			
Wear leayer material /	Hardwood / 3.5 mm			
thickness				
Resandable	2 times			
Core material	Pine			
Hardness (Brinell) value /	3,7 / 2.2 - 5.9			
range				
Warranty	30 years			

DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.


Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection



OAK STUDIO AB MATT