

CHEVRON GREY

Warm brownish grey floor with occasional knots, cracks and fillings. This is a frame board which is supplied in form of a plank, it can be used to create a boarder around the Chevron patterned design. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	151XADEKWKKW190 / 7393969041850	range		
Design / Wood Species	Chevron / White Oak	Warranty	20 years	
Surface Treatment /	Oil / Stained	TECHNICAL PROPERTIES	5	
Natural/Stained		Moisture content	EN13183	7%±2%
Refining Treatment	Beveled 4-sided, Brushed		LIVIDIOD	
Width x Length x Thickness	5 7/8 x 74 3/4 x 5/8"	—— Minimun Mean Density —— kg/m³		>500 kg/m ³
Weight per package / per	40.1 lbs / 17.4 lbs	Reaction To Fire	EN13501-1	Dfl-s1
m2		Formaldehyde Emission	EN717-1	E1
Area per package / per	24.8 sqft / 1162.5 sqft	Content PCP	CEN/TR14823	≤ 5 x 10-6n
pallet		Breaking Strength N/mm ²	EN1533	NPD
Grading	Lively	— Thermal Resistance R-Value		.11 (m2K/W)
Joint	Tongue & Groove	Biological Durability	EN350-2	Class 1
Installation method	Glue-Down	— CARB2	L11330 Z	Compliant
Floor heating	Yes	Slip resistance	CEN/TS15676	NPD
Wear leayer material /	Hardwood / 1/8"	— Slip resistance	CEN/13130/0	NPD
thickness		TSCA MARSON CLASS		
Resandable	2 times	CARB P2 Compliant		
Core material	Poplar			
Backside material	Oak			

DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

